
TECHNICAL DATA Boflex



Performance according to EN14904		Shock absorption		Deformation		Friction	Ball bounce	Rolling load
		TYPE 3 : ≥ 40% ≤ 55%	TYPE 4: ≥ 55% ≤ 75%	TYPE 3: ≥ 1.8mm ≤ 3.5mm	TYPE 4: ≥ 2.3mm ≤ 5.0mm	80 - 110	≥ 90%	Min. 1500N
Boflex	CHAMPION		58%		2.6mm	-	93%	ОК







Double tongue & groove



* FSC™ Mix 70%

Package overview

Pack size: 6 boards = 1.81 m² (25 kg) Pallet size: 49 packs = 88.69 m² (1225 kg)

Supplied: Boflex adhesive and perimeter support strips.

We reserve the right to deliver up to 10 % in lengths from 70cm to 150cm.

Boflex Champion Construction Details (from the top to the edge of concrete/subfloor) Height						
Boflex Champion • Plywood board • 2 strips of Evazote 50 are glued into the board	Boflex size: 26 x 137 x 2200mm Boflex Champion board 21mm + Evazote 5mm (Board dimensions: 21 x 137 x 2200mm + Evazote dimensions: 8 x 10mm and 11 x 9mm)	26mm				
Perimeter strips	4.4 x 22 x 1500mm	\checkmark				
PE foil (ordered separately)	Special requirement for new buildings: 2 layers of 0.2mm. It is not a moisture barrier, but gives to the floor an extra protection.	0.4mm				
Construction height		26mm				

BOEN AS EN 14904 DOP 4658

MAINTENANCE

We recommend starting a regular system of maintenance from day one. The amount of maintenance your floor requires will depend on how you use and treat it. For more information: boensport.com

The environment is at the core of all we do.

BOEN hardwood flooring is a product of nature. As a procurer of timber BOEN has an important heritage to maintain. Constant involvement in resource preservation methods, participation in reforestation programmes and the development of alternatives to exotic species shows Boen's dedication towards the environment.

All timber purchased by BOEN is supplied from sources who belong to one or more forestry schemes or are working towards certification.

BOEN Bruk (Norway) FSC™ C051117, BOEN Parkett Deutschland (Germany) FSC™ C101713, BOEN Lietuva (Lithuania) FSC™ C021510, BOEN UK FSC™ C047288, BOEN US FSC™ C095158. www.fsc.org, FSC – The mark of responsible forestry.







